



| CKTS | DIM A | DIM B | DIM C | DIM D |
|------|-------|-------|-------|-------|
| 6 | 2.50 | 4.50 | 3.60 | 6.00 |
| 7 | 3.00 | 5.00 | 4.10 | 6.50 |
| 8 | 3.50 | 5.50 | 4.60 | 7.00 |
| 9 | 4.00 | 6.00 | 5.10 | 7.50 |
| 10 | 4.50 | 6.50 | 5.60 | 8.00 |
| 11 | 5.00 | 7.00 | 6.10 | 8.50 |
| 12 | 5.50 | 7.50 | 6.60 | 9.00 |
| 13 | 6.00 | 8.00 | 7.10 | 9.50 |
| 14 | 6.50 | 8.50 | 7.60 | 10.00 |
| 15 | 7.00 | 9.00 | 8.10 | 10.50 |
| 16 | 7.50 | 9.50 | 8.60 | 11.00 |
| 17 | 8.00 | 10.00 | 9.10 | 11.50 |
| 18 | 8.50 | 10.50 | 9.60 | 12.00 |
| 19 | 9.00 | 11.00 | 10.10 | 12.50 |
| 20 | 9.50 | 11.50 | 10.60 | 13.00 |
| 21 | 10.00 | 12.00 | 11.10 | 13.50 |
| 22 | 10.50 | 12.50 | 11.60 | 14.00 |
| 23 | 11.00 | 13.00 | 12.10 | 14.50 |
| 24 | 11.50 | 13.50 | 12.60 | 15.00 |
| 25 | 12.00 | 14.00 | 13.10 | 15.50 |
| 26 | 12.50 | 14.50 | 13.60 | 16.00 |
| 27 | 13.00 | 15.00 | 14.10 | 16.50 |
| 28 | 13.50 | 15.50 | 14.60 | 17.00 |
| 29 | 14.00 | 16.00 | 15.10 | 17.50 |
| 30 | 14.50 | 16.50 | 15.60 | 18.00 |
| 31 | 15.00 | 17.00 | 16.10 | 18.50 |
| 32 | 15.50 | 17.50 | 16.60 | 19.00 |
| 33 | 16.00 | 18.00 | 17.10 | 19.50 |
| 34 | 16.50 | 18.50 | 17.60 | 20.00 |
| 35 | 17.00 | 19.00 | 18.10 | 20.50 |
| 36 | 17.50 | 19.50 | 18.60 | 21.00 |
| 37 | 18.00 | 20.00 | 19.10 | 21.50 |
| 38 | 18.50 | 20.50 | 19.60 | 22.00 |
| 39 | 19.00 | 21.00 | 20.10 | 22.50 |
| 40 | 19.50 | 21.50 | 20.60 | 23.00 |
| 41 | 20.00 | 22.00 | 21.10 | 23.50 |
| 42 | 20.50 | 22.50 | 21.60 | 24.00 |
| 43 | 21.00 | 23.00 | 22.10 | 24.50 |
| 44 | 21.50 | 23.50 | 22.60 | 25.00 |
| 45 | 22.00 | 24.00 | 23.10 | 25.50 |
| 46 | 22.50 | 24.50 | 23.60 | 26.00 |
| 47 | 23.00 | 25.00 | 24.10 | 26.50 |
| 48 | 23.50 | 25.50 | 24.60 | 27.00 |
| 49 | 24.00 | 26.00 | 25.10 | 27.50 |
| 50 | 24.50 | 26.50 | 25.60 | 28.00 |

- Note:
- Material:
 - Housing: thermoplastic high temp. UL94V-0; Color: natural.
 - Terminal: copper alloy T=0.20mm
 - Fitting Nail: copper alloy T=0.30mm
 - Finsh:
 - Terminal: Underplating: matt Tin overall.
 - Fitting Nail: Underplating: matt Tin overall.
 - Product must comply HF RoHS specification.

PART NO. SPEC
 AFC18-SXX X X X-HF

NO. OF CKTS
 CONTACT TYPE
 PLATING CODE

PACKING CODE
 A:Tape & Reel
 B:Tray package
 C:Tube
 E:Tape & Reel with Mylar
 F:Box with Mylar
 G:Tube with Mylar

1:GOLD FLASH 1u"
 2:GOLD FLASH 2u"
 3:GOLD FLASH 3u"
 C:MATT-Tin 90-120u"

| CUSTOMER DRAWING | |
|------------------------------|-------------------|
| Tolerance Unspecified (未注公差) | Size (图幅): A4 |
| 0.0 ±0.15 0° ±5° | Unit (单位): MM |
| 0.00 ±0.10 0° 0 ±3° | Scale (比例): 1:1 |
| 0.000 ±0.05 0° 0.00 ±1° | Page (页数): 1 OF 1 |
| Project View (投影视角) | Rev (版本): A |

浙江合丰科技有限公司
 HEFENG Zhejiang Hefeng Technology Co.,Ltd

Product Name (产品名称): 0.5Pitch H=4.0 FPC Non-ZIF CONN. SA SMT Reverse TYPE

Product No (产品料号): AFC18-S**JCA-HF

| Rev 版本 | Change Description 变更内容 | Date 日期 | Revisor 制/修订人 |
|--------|-------------------------|------------|---------------|
| A | 初版发行 | 2011/12/23 | Allan |

| Designer (设计): | Checked (审核): | Approved (核准): |
|-----------------|----------------|----------------|
| Steven 12/23'11 | Allan 12/23'11 | |